

# APEX RACING 2 STROKE

## TECHNICAL DATA SHEET

V.01/2024  
1014



A premium motor oil designed for performance two stroke engines.

### DESCRIPTION

APEX RACING 2 STROKE is an advanced, high performance fully synthetic motor oil for all two-stroke motors, incorporates a strong detergent and extreme pressure additive package which affords increased protection against piston seizure, ring sticking, engine deposits and exhaust blocking. The lubricant is designed to provide outstanding film strength with extremely low ash content. It is specifically suitable for air-cooled engines such as motorcycles, lawn mowers, brush cutters and chainsaws. It is suitable for engines which are lubricated either by auto lube systems or petrol/oil mixtures.

### ADVANTAGES / CUSTOMER BENEFITS

- Excellent lubricating properties
- Excellent detergent properties

### APPROVALS / PERFORMANCE STANDARDS / SPECIFICATIONS

- JASO FD
- API-TC
- ISO EGC & EGD
- T.I.S.I. (1040)

### ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Safety Data Sheet (SDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. Ensure appropriate personal safety equipment is used when handling the product.

This product has a shelf life of 36 months when stored in a dry environment at ambient temperatures (10-30°C).

### TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	METHOD	UNITS	RESULT
ISO/SAE Grade			100
Viscosity @ 40°C	ASTM D 2983	cSt	101
Viscosity @ 100°C	ASTM D 2983	cSt	18
Viscosity Index	ASTM D2270-77		145
Pour Point °C	ASTM D97	°C	-12.0
Flash Point °C	ASTM D93	°C	210
Density @ 20°C	ASTM D792	g/ml	0.85
Appearance	Visual		Bright & Clear
Colour	Visual		Blue

### PACKAGING

5L / 20L / 210L / 1000L

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.



Copyright © 2024

PHONE +27 11 827 5935  
EMAIL [jhb@swifts.co.za](mailto:jhb@swifts.co.za)  
ADDRESS 1 Molten St, Delville Ext 4, Germiston  
Johannesburg, South Africa

