



1 Molten Street, Delville Ext. 4, Germiston

Po Box 23 , Germiston 1400

Tel: (011) 827-5935

Fax: (011) 824-2125

Fax to Email 0866714060

E-mail: [jhb@swifts.co.za](mailto:jhb@swifts.co.za)

**web site [www.swifts.co.za](http://www.swifts.co.za)**

**PRODUCT DATA**

# LITHIUM COMPLEX HDX 2 EXTRA

## HIGH PERFORMANCE MOLYBDENUM DISULPHIDE FORTIFIED GREASE

### DESCRIPTION

A blue-black no 2 consistency lithium complex soap thickened product with a ISO 460 mineral base oil. Corrosion inhibitors and adhesion improver contribute to the products performance.

### TYPICAL SPECIFICATIONS

TEST	RESULT
Colour	Black
NLGI	2
Worked Penetration	260 / 300
Density 20°C	0,916
Base Oil Viscosity at 40°C	460
<b>Temperature</b>	
Service Temperature °C	-23 to +140
Drop point °C min	>250
<b>Load-carrying capacity, wear protection, service life</b>	
Four ball tester	
Weld load Kg	480-500
Wear scar	0,5
Timken OK Load lb	40
<b>Speed</b>	
DN Value mm/min	200000
<b>Resistance</b>	
Water resistance, dynamic, 80°C	1
Oxidation resistance	
Pressure drop 100 h, 99°C bar	0,35
<b>Corrosion protection</b>	
SKF - Emcor method	
Degree of corrosion DIN 51802	0

### COMPOSITION

- Corrosion inhibitor
- Solids
- Mineral oil with ester
- Lithium complex soap
- Adhesion improver
- EP additives

### BENEFITS

High load-carrying capacity in shock loaded conditions. Owing to the presence of extreme pressure additives, and solid lubricants it improves wear protection. Very good adhesion strength. Suitable for long-term lubrication. Very good corrosion protection and water resistance. Excellent mechanical stability for extended service life.

### APPLICATIONS:

Bearings: Heavy Duty Anti-friction, slow to medium speed.  
 Plain  
 Heavily loaded bearings.  
 subjected to vibration and high temperature.  
 Splines: Where there is a risk of fretting corrosion.  
 Earth moving machines - pins and bushes.  
 Mining machines including crusher and shaker screen bearings.  
 Conveyor rollers, Cranes, Forklifts.  
 Lubricating grease for highly loaded metal to metal combinations.  
 Open Gears

### PACKAGING

180Kg

18 Kg