



1 Molten Street, Delville Ext. 4, Germiston

Po Box 23 , Germiston 1400

Tel: (011) 827-5935

Fax: (011) 824-2125

Fax to Email 0866714060

E-mail: jhb@swifts.co.za

[web site www.swifts.co.za](http://www.swifts.co.za)

PRODUCT DATA

ANTI SEIZE NON METALLIC

DESCRIPTION

A solid lubricant black paste with low levels of sulphur chlorine and fluorine. No lead or nickel is contained in this product.

APPLICATIONS:

For nickel alloy nuts, bolts and threaded fasteners subjected to high temperatures typically used on gas and steam flanges.

APPLICATION INFORMATION:

Used bolts to be cleaned with a wire brush.
New bolts must be degreased.
Use a clean brush to spread sufficient product on the thread to ensure good seal. As this is an ultra pure product please see that the brush is not contaminated with other oils, products or chemicals.

PACK SIZE

500G	1 700 4680
1KG	1 700 4681
5KG	1 700 4752
20KG	1 700 4753

BENEFITS:

- Easy loosening even after long periods of use.
- Prevents solder embrittlement.
- Can be used up to 1300°C.
- No ingredients considered a health hazard.
- Prevents stress cracking.
- Accurate torque tensioning.

COMPOSITION:

Mineral oil.
Solid lubricants.
Synthetic oil.
Tackyfier
Thickener

TYPICAL SPECIFICATIONS:

Colour	Black
Unworked penetration	260-300
Density @ 20°C	1.16
Service temperature	-35 to 1300°C
Weld load N	4000
Wear scar 800N load	1.6