

STANDARD DUTY MOTOR OIL 15W40 (CF)



TECHNICAL DATA SHEET

V.01/2024
993

A mineral motor oil lubricant for diesel engines for most on-road and stationary applications.

DESCRIPTION

STANDARD DUTY MOTOR OIL 15W40 (CF) is an advanced heavy duty, multigrade diesel engine oil, designed for direct injection, turbocharged engines.

ADVANTAGES / CUSTOMER BENEFITS

- Exceeds all major American, European and Japanese OEM and industry specifications
- Excellent performance with extended oil drain intervals on low emission engines.
- Combination of detergent and dispersant additives maintains power output by providing excellent control over ring and ring groove deposits which can affect engine operation.
- Multigrade viscosity allow for maximum lubricity in all areas of the engine.
- High oxidation stability, effective control over high temperature piston deposits, wear, corrosion, foaming and soot accumulation.
- Superior de-aeration and anti-foam characteristics for accurate operation of hydraulic actuated fuel injection systems.

APPROVALS / PERFORMANCE STANDARDS / SPECIFICATIONS

- API SJ/CF
- ACEA A2
- Mack EO-L
- MAN 271
- MB-Approval 228.1
- Volvo VDS

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Safety Data Sheet (SDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. Ensure appropriate personal safety equipment is used when handling the product.

This product has a shelf life of 36 months when stored in a dry environment at ambient temperatures (10-30°C).

TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	METHOD	UNITS	RESULT
ISO/SAE Grade			15W40
Viscosity @ 40°C	ASTM D 2983	cSt	105
Viscosity @ 100°C	ASTM D 2983	cSt	14
Viscosity Index	ASTM D2270-77		125
Pour Point °C	ASTM D97	°C	-39.0
Flash Point °C	ASTM D93	°C	240
Density @ 20°C	ASTM D792	g/ml	0.89
Appearance	Visual		Bright & Clear
Colour	Visual		Dark Yellow

PACKAGING

5L / 20L / 210L / 1000L

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.



INDUSTRIAL (PTY) LTD

Copyright © 2024

PHONE +27 11 827 5935
EMAIL jhb@swifts.co.za
ADDRESS 1 Molten St, Delville Ext 4, Germiston
Johannesburg, South Africa

