

STANDARD HYDRAULIC OIL 32

TECHNICAL DATA SHEET

V.01/2024
977



A high performance anti-wear hydraulic oil.

DESCRIPTION

STANDARD HYDRAULIC OIL 32 contains a premium additive package and carefully selected group II base oils, specifically designed to meet or exceed the performance requirements of all major hydraulic equipment manufacturers and industry organisation specifications. It is designed for the requirements of today's modern hydraulic high pressure pumps and systems. The product has the capability to provide performance reserve, leading to long oil and filter life and ensuring unsurpassed equipment protection.

ADVANTAGES / CUSTOMER BENEFITS

- Excellent oxidation stability
- Capable to extend the oil drain interval
- Good sludge and particulate control
- Improved filterability and consequently less downtime
- Improved protection of critical components with tight tolerances
- Superior wear protection for maximum equipment life
- Greater energy saving potential
- Excellent hydrolytic stability for improved protection
- Good anti-foam and air release properties.
- Good demulsibility ensuring rapid water separation.

In addition to meeting all major global hydraulic performance specifications, this product reduces wear, valve sticking, metal transfer and filterability issues; handles more demanding duty cycles; and resists oil degradation at higher operating temperatures.

APPROVALS / PERFORMANCE STANDARDS / SPECIFICATIONS

Denison HF-0, HF-1 and HF-2
Cincinnati Machine P-68, P-70, P-69
Eaton Brochure 694 for 35VQ25A (formerly M-2950-S and I-286-S)
DIN 51524 Part 2 (HLP) & Part 3 (HVLP)
GM LS2
ISO 11158 Categories HM and HV
ASTM D 6158 Type HM and HV
AFNOR NF E 48-603 HM and HV

ISO 6743/4 HM
ISO 11158 HM
DIN 51524 P2 HLP

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Safety Data Sheet (SDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. Ensure appropriate personal safety equipment is used when handling the product.

This product has a shelf life of 36 months when stored in a dry environment at ambient temperatures (10-30°C).

TYPICAL TECHNICAL CHARACTERISTICS

| DESCRIPTION | METHOD | UNITS | RESULT |
|-------------------|---------------|-------|----------------|
| ISO/SAE Grade | | | 32 |
| Viscosity @ 40°C | ASTM D 2983 | cSt | 32 |
| Viscosity @ 100°C | ASTM D 2983 | cSt | 6 |
| Viscosity Index | ASTM D2270-77 | | 109 |
| Pour Point °C | ASTM D97 | °C | -42.0 |
| Flash Point °C | ASTM D93 | °C | 227 |
| Density @ 20°C | ASTM D792 | g/ml | 0.86 |
| Appearance | Visual | | Clear & Bright |
| Colour | Visual | | Pale Yellow |

PACKAGING

5L / 20L / 210L / 1000L

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.



Copyright © 2024

PHONE +27 11 827 5935
EMAIL jhb@swifts.co.za
ADDRESS 1 Molten St, Delville Ext 4, Germiston
Johannesburg, South Africa

