

# SUPER DUTY GEAR OIL 68

## TECHNICAL DATA SHEET

V.01/2024  
1015



**An industrial gear oil for all types of enclosed-gear drives with circulation or splash lubrication systems.**

### DESCRIPTION

SUPER DUTY GEAR OIL 68 is a high performance, high quality, extreme pressure (EP), industrial gear oil, blended using high quality base oils and sulphur-phosphorus, anti-rust, anti-oxidant and anti-corrosion additives to meet the requirements of most industrial gears.

### ADVANTAGES / CUSTOMER BENEFITS

Specifically designed for:

- Spur, bevel, helical, worm and industrial hypoid gear cases
  - Enclosed industrial gear drives
  - Open gear drives (heavy grades)
  - Plain and rolling element bearings
  - For both circulation and splash lubrication
- 
- Highly effective EP protection and anti-wear performance because the oil forms a protective film in areas of metal-to-metal contact.
  - Effective oxidation inhibitors and copper passivator minimises oil oxidation and therefore extends oil drain intervals.
  - High thermal stability EP system ensures clean gear and bearing surfaces.
  - Rapid water shedding properties ensures high resistance to emulsion formation.

### APPROVALS / PERFORMANCE STANDARDS / SPECIFICATIONS

- AGMA 9005-E02
- ISO 12925-1 CKC
- ISO 6743-6 CKC
- AIST 224
- DIN 51517 Part III

### ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Safety Data Sheet (SDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. Ensure appropriate personal safety equipment is used when handling the product.

This product has a shelf life of 36 months when stored in a dry environment at ambient temperatures (10-30°C).

### TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	METHOD	UNITS	RESULT
ISO/SAE Grade			68
Viscosity @ 40°C	ASTM D 2983	cSt	68
Viscosity @ 100°C	ASTM D 2983	cSt	9
Viscosity Index	ASTM D2270-77		102
Pour Point °C	ASTM D97	°C	0.0
Flash Point °C	ASTM D93	°C	0
Density @ 20°C	ASTM D792	g/ml	0.85
Appearance	Visual		Bright & Clear
Colour	Visual		Dark Yellow

### PACKAGING

5L / 20L / 210L / 1000L

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.



INDUSTRIAL (PTY) LTD  
INDUSTRIAL (PTY) LTD

Copyright © 2024

PHONE +27 11 827 5935  
EMAIL jhb@swifts.co.za  
ADDRESS 1 Molten St, Delville Ext 4, Germiston  
Johannesburg, South Africa

