

SUPER DUTY OG/WR GREASE

TECHNICAL DATA SHEET

V.01/2024

916



High quality multi purpose grease with solids suitable for wire ropes, open gears, 5th wheels, and application with heavy loads. A tenacious tacky, stay in place grease.

DESCRIPTION

SUPER DUTY OG/WR GREASE is manufactured using highly refined mineral base oils which are carefully selected and then fortified with synthetic polymers, producing a highly shear stable foundation for the grease. This base oil foundation allows the product to perform in applications where heavy duty loads are typical.

SUPER DUTY OG/WR GREASE is manufactured using a lithium calcium thickener resulting in a buttery appearance with excellent shear stability characteristics. In addition, this type of thickener is easily pumped, has a moderate resistance to heat and exhibits excellent water resistance. The optimal operating conditions for this grease in terms of temperature, is from -30 to 130 degrees celcius, however short periods of elevated temperatures can be tolerated without severe damage to the product.

SUPER DUTY OG/WR GREASE is manufactured to a NLGI 2 grade resulting in a grease of medium to soft consistency. The product contains a blend of synthetic tackifiers, increasing it's ability to resist water and adherence with all surfaces.

SUPER DUTY OG/WR GREASE is tan in colour and whose formulation includes a full treat of extreme pressure (EP) and corrosion preventative additives enabling the grease to meet or exceed internationally recognised performance standards. In addition this product is fortified with graphite making it suitable for boundary lubrication at high temperatures and/or heavy loads. In the case of accidental overheating, the presence of this material will still guarantee good lubrication and avoid any jamming or sticking.

KEY ADVANTAGES

Thermal stability	Very good thermal stability allowing the grease to perform for short periods of time under extreme temperatures, regaining its original texture after cooling to ambient temperature.
Mechanical stability	Allows for long periods of storage or non-use in the application without and mechanical breakdown of the grease thickener (e.g. oil separation)
Anti-corrosive properties	Exhibits very good to excellent anti-rust and anti-corrosion properties.
Water resistant	The thickener has very good natural attributes which displace and resist water ingress.
Heat resistant	Exhibits excellent resistance to heat.

TYPICAL APPLICATIONS

For use on wire ropes, high load carrying capability, good protection against wear from rubbing one against the other.

Meets US Steel Specification 405-406 for wire ropes

Designed for use on ropes operating in Marine and other arduous environmental conditions on equipment such as hoists, drag lines, cranes, ships and ship hoists

Heavy duty applications in the mining and construction industry.

Can be used in open gears, pantographs, pump glands, link pins, bushes and linkages. In addition, it can be used as a rail and flange lubricating equipment.

For the lubrication of 5th wheels, king pins, tractor-trailer turnables, shackle pins, etc...

TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	METHOD	UNITS	RESULT
NLGI Grade	ASTM D 217		2
Thickener Type			Lithium Calcium
Colour	Visual		Tan
Appearance	Visual		Buttery, Tacky
Penetration	ASTM D 217	0.1mm	280
Dropping Point	ASTM D 2265	°C	190
Viscosity of Oil @ 40°C	ASTM D 2983	cSt	500
4-Ball Wear Test Scar	ASTM D 2266	mm	0.45
4-Ball Weld Load	ASTM D 2596	kg	315
Timken OK Load	ASTM D 2509	lb	45
Corrosion Prevention	ASTM D 1743		Pass
Copper Strip Corrosion	ASTM D 4048		1B

SPECIFICATIONS

ASTM D-5864 / CEC L-33-T-82

KPF2M-30 (DIN 51825)

ISO-L-X-CCIB2 (ISO 6743-9)

PACKAGING

100g tubes

500g Tubs (12 per box)

4.5kg Plastic Pail

15kg Steel pails

18kg Plastic pails

50kg Steel drums

180kg Steel open top drums

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

COMPATIBILITY

Mixing greases in a system can cause issues with thickener systems reacting with each other, changing the physical and chemical structure of the grease, causing an inability to hold or release base oil. Proper care must be taken to ensure compatibility when changing from one grease system to another.

This grease is not compatible with greases making use of the following thickener types: barium, bentonite clay, aluminium complex and polyurea. There is a borderline compatibility with calcium and sodium thickeners. Care must be taken to ensure the application is properly cleaned before using this product if a borderline or non-compatible product has been used before.

ENVIRONMENT, HEALTH and SAFETY

This product is classified under the OECD 301B Modified Sturm, ASTM D-5864, and CEC L-33-T-82 standards as being inherently biodegradable (i.e. 20-70% biodegradable in 28 days). Information is available on this product in the Material Safety Data Sheet (MSDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. This product contains no PCB's (Polychlorinated Biphenyls).

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.