

SUPER DUTY STOU 15W40

TECHNICAL DATA SHEET

V.01/2024
1004



A STOU (Super Tractor Oil Universal), designed for turbocharged or naturally-aspirated diesel engines, adapted for mechanical transmissions, gearboxes, reduction drives and bevel gears.

DESCRIPTION

SUPER DUTY STOU 15W40 is a multigrade, multi-purpose oil for the lubrication of agricultural tractors and farm equipment. This universal oil offers wear and friction control for the transmissions including power-shift models, diesel and petrol engines, gear drive units, wet brake systems, hydraulic and power steering units for farm tractors and equipment.

ADVANTAGES / CUSTOMER BENEFITS

- Single oil for the majority of farm equipment
- Excellent diesel engine performance
- High load carrying capacity in transmissions
- Reduces chatter in wet brake systems
- High thermal stability

APPROVALS / PERFORMANCE STANDARDS / SPECIFICATIONS

- APICG-4/SF; GL4
- John DeereJDM J27
- Massey FergusonCMS 1145, 1144, 1139
- AllisonC-4
- ZFZF TE-ML-06A/B/C/D; 07B
- MILMIL-L-2104D
- CaterpillarTO-2
- ACEAE2
- MB227.1, 228.1, 228.3
- MAN271

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Safety Data Sheet (SDS). Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. Ensure appropriate personal safety equipment is used when handling the product.

This product has a shelf life of 36 months when stored in a dry environment at ambient temperatures (10-30°C).

TYPICAL TECHNICAL CHARACTERISTICS

DESCRIPTION	METHOD	UNITS	RESULT
ISO/SAE Grade			15W40
Viscosity @ 40°C	ASTM D 2983	cSt	99
Viscosity @ 100°C	ASTM D 2983	cSt	14
Viscosity Index	ASTM D2270-77		124
Pour Point °C	ASTM D97	°C	-39.0
Flash Point °C	ASTM D93	°C	240
Density @ 20°C	ASTM D792	g/ml	0.87
Appearance	Visual		Bright & Clear
Colour	Visual		Dark Yellow

PACKAGING

5L / 20L / 210L / 1000L

Misrepresentation Act 1967. Trade description Act 1968. The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason no warranty is given, express or implied. This information sheet was prepared from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.



INDUSTRIAL (PTY) LTD

Copyright © 2024

PHONE +27 11 827 5935
EMAIL jhb@swifts.co.za
ADDRESS 1 Molten St, Delville Ext 4, Germiston
Johannesburg, South Africa

