



1 Molten Street, Delville Ext. 4, Germiston

Po Box 23 , Germiston 1400

Tel: (011) 827-5935

Fax: (011) 824-2125

Fax to Email 0866714060

E-mail: jhb@swifts.co.za

[web site www.swifts.co.za](http://www.swifts.co.za)

PRODUCT DATA

UT-600-CORR-OIL

DESCRIPTION

- An anti-corrosion red ultra thin film fluid offering reliable corrosion protection for machines and machine elements during intermediate storage and transportation.
- Water displacement properties instantly dry and protect newly machined parts.

ADVANTAGES

- Easily applied by dipping painting or spray.
- Can be removed simply by wiping with a cloth or with any hydrocarbon solvent for pre-paint preparation.
- Characterised by quick penetration even in areas difficult to access. It loosens rusted or frozen screw connections as well as other components, thus facilitating non-destructive disassembly.
- It's adhesive properties to all metallic surfaces provides excellent corrosion protection.

PACKINGS AND PART NO'S

5L	1-7009571
25L	1-7009572
210L	1-7009573

PHYSICAL PROPERTIES

- Fluid lubricant.
- Protects metals from corrosion.
- Dissolves rust.
- Displaces water.
- Solvent cleaner.

APPLICATIONS

- Corrosion protection for:
 - ** Dies, chucks and drilling equipment, fittings tools and machines.
 - ** Electrical components, connectors, relays, switches and fine precision instruments.
 - ** Newly machined parts.
 - ** All metallic parts that are manufactured, transported or stored.

TYPICAL PROPERTIES

TEST	UNIT	RESULT
Density @ 20°C ASTM D 1298		0,745
Flash Point °C C.o ASTM D95		37,5
Viscosity @ 40°C ASTM D 455cst		1,6