



1 Molten Street, Delville Ext. 4, Germiston  
Po Box 23 , Germiston 1400  
Tel: (011) 827-5935 /6/7  
Fax: (011) 824-2125  
Fax to Email 0866714060  
E-mail: [jhb@swifts.co.za](mailto:jhb@swifts.co.za)  
**Web site [www.swifts.co.za](http://www.swifts.co.za)**

## PRODUCT DATA

# ZP ZINC PROTECTOR PLUS

**Zinc coating with microfine zinc powder in an organic binder,  
for all kinds of metal surfaces.**

## APPLICATION

Protects bare metal surfaces from corrosion after drilling and welding. Repairs damaged galvanized surfaces. Anti corrosion primer for any type of car finish or paint coating.

## COMPOSITION

- Zinc powder.
- Solvent.
- Organic resin.
- Suspension medium.

## TYPICAL PROPERTIES

TEST	UNIT	RESULT
Colour		Grey
<b>Density, viscosity</b>		
Density @ 20°C	g/ml	1.22
<b>Temperature</b>		
Service temp range	°C	-40 to 500

### Anti Corrosion Standard

Tested to conform to and exceed the requirements of DIN 50 021

## PACKAGING

400ml	1 - 700 9870
1L	1 - 700 9871
5L	1 - 700 9872

## FEATURES

- Excellent adhesion to oil and grease free surfaces. Fast drying.
- Provides permanent protection against corrosion and rusting,
- Cathodic -corrosion protection. Protects metal from rust even when the surface is scored or damaged.
- Resists salt water.
- Thermally stable up to + 500°C.

## HOW TO APPLY

Stir bulk packaging thoroughly before use. Clean grease off with a non petroleum solvent and remove any rust residues. Apply by painting, spraying, dipping or from the aerosol can.

It is touch-dry after 15 minutes at 20°C. Shake spray can before use. Spray a thin layer evenly from a distance of 20 to 25cm. After use clean the spray can valve by turning the can upside down and pressing nozzle until actuator is clear.

## USABLE LIFE AND STORAGE

When stored at or below 20°C in the original unopened containers this product has a usable life of 24 months from the date of production.